



2nm 135° White, stern, black anodized

301-006-B

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.

Vertically mounted with 2,5m cable

| Specifications | |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number | 301-006-B |
| Light Color | White |
| Dimensions metric | 86,2 x 28 x 57,75 |
| Certification | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support |
| Intensity | >5.4cd |
| Dimensions imperial | 3.3" x 1.1" x 2.27" |
| Approved to | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| Visibility | 2nm |
| Included In Package | 1 Navigation light, precabled with 2.5 meter shielded marine grade cable, 2 Mounting screws (M6 * 8 mm), Installation guide |
| Operating temperature | -25°C to 55°C |
| Mounting | Vertical |
| Materials | Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| Operating Voltage | 10-32VDC |
| EAN | 5704438009752 |
| IP rating | IP68 |
| Power draw (W) | 1,3 |
| UPC Code | 879343009755 |
| Connection | 2.5m cable |

| Specifications | |
|-----------------------------------------|--------------------------|
| Current consumption (mA @ 12VDC) | 110 |
| Stock status | Usually in stock |
| Lead time | 1-2 weeks |
| Current consumption (mA @ 24VDC) | 50 |
| Vessel size | Under 12M,12-20M,20-50M |
| Min. feed wire gauge | 0.5mm ² AWG22 |
| Weight (Kg) | 0.42 Kg |
| Weight (Oz) | 14.81 Oz |